

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-173645

(43)Date of publication of application : 23.06.2000

(51)Int.Cl.

H01M 10/30

B60L 11/18

(21)Application number : 10-346828

(71)Applicant : YUASA CORP
HONDA MOTOR CO LTD

(22)Date of filing : 07.12.1998

(72)Inventor : KISHIMOTO NORIYOSHI
HINO YUZO
ITO TAKASHI
OSHITANI MASAHIKO
SATO NOBORU
YAGI KAZUHIKO

(54) NICKEL-HYDROGEN BATTERY FOR ELECTRIC VEHICLE

(57)Abstract:

7 of 10 p

PROBLEM TO BE SOLVED: To obtain a single nickel-hydrogen battery for an electric vehicle, having both a high output density and a high energy density, superior in charging/discharging efficiency and heat radiation characteristic, capable of being mounted even in a low-profile automobile, superior in reliability, and capable of securing traveling distance per one charge operation of about 100 km or more.

SOLUTION: In this single nickel-hydrogen battery 10, constituting an assembled battery mounted in an electric vehicle, a height H is set at 140 mm or less, the width of an electrode plate is less than a height thereof, the number of the positive electrode plates is 15-30, the number of the negative electrode plates is 16-31, the distance between two electrode plates is 0.1-0.2 mm, and a battery capacity is 30-80 Ah.

